

AC-DC 24W


3A-242WUXX

Features:

- Universal AC Input 90~264Vac
- Low ripple noise
- Meet CEC requirement
- 100% burn in test
- 1 year warranty
- UL,cUL,CB,PSE,FCC
- Meet EPS 2.0 LEVEL V



Dimension:



Model No.	Output		Additional Safety
	Voltage	Current	
3A-242WU10	10V	2.0A	
3A-242WU12	12V	2.0A	
3A-242WU15	15V	1.6A	
3A-242WU16	16V	1.5A	
3A-242WU24	24V	1.0A	

Specification:

REV.01 2010.01.15

Input	Voltage	AC 90V~264V Universal full range
	Frequency	47-63Hz
	Current	800mA
	Leakage Current	< 0.25mA
Others	Start up time	< 2000mS @Rated minimum AC input
	Rise time	< 50mS
	Hold up time	>10mS @ 110Vac/60Hz input
	Cooling	Natural Cooling
Environment	Temperature	Operating: 0~40°C;Storage: -10~+75°C
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Converting)
M.T.B.F	50k Hours	
Safety	UL 60950-1,CSA C22.2 No.60950-1,-1,IEC 60950-1	
EMC	EMI	FCC PART 15 , EN55022 , EN61000-3
	EMS	EN55024(EN61204-3) EN61000-4