

AC-DC MINI 40W


3A-403DAXX

Features:

- Universal AC Input 90~264Vac
- Low ripple noise
- No minimum load requirement
- 100% burn in test
- 1 year warranty
- UL,cUL,GS,CB,CE,FCC standard
- Meet EPS 2.0 LEVEL V



Dimension:



Model No.	Output		Additional Safety
	Voltage	Current	
3A-403DA12	12V	3.3A	
3A-403DA19	19V	2.1A	
3A-403DA20	20V	2.0A	
3A-403DA24	24V	1.7A	
3A-403DA48	48V	0.85A	

Specification:

REV.03 2010.9.16

Input	Voltage	AC 90V~264V Universal full range
	Frequency	47-63Hz
	Current	1A
	Leakage Current	< 0.25mA
Others	Start up time	< 2000mS @ Minimum AC input
	Rise time	< 20mS
	Hold up time	> 20mS @ 230Vac/50Hz input
	Cooling	Natural Cooling
Environment	Temperature	Operating: 0~40°C;Storage: -10~+75°C
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Converting)
M.T.B.F	50k Hours	
Safety	UL 60950-1,CSA C22.2 No.60950-1,EN60950-1,IEC 60950-1	
EMC	EMI	FCC CFR 47 PART 15 , EN55022 , EN61000-3
	EMS	EN55024(EN61204-3) EN61000-4